

圆形冷却水塔 Round Cooling Tower

冷却塔采用优质PVC散热胶片、且设计形状更有效地延长高温水跟冷却风接触时间，所以冷却效果特佳。外壳底盘采用优质高强度玻璃纤维制成，外形美观，防腐及抵抗外界恶劣环境能力特强，转动及接合部分采用优质原材料加工，大大提高使用寿命及接合强度，客服部提供24小时技术及维修售后服务，将大大提高工作效率。

Our cooling tower adopts high quality PVC heat radiation films and the designed shape offilms effectively prolongs the contact time between high temperature water and the cooling air, therefore the cooling effect is excellent. The tower chassis, featuring anti--corrosion, strong abilityof resistance of vile weather and beautiful appearance made of high strength glassfiber, and itsrotation part and connection area is made of high quality raw materials, that greatly improves theservice life and connection strength.



参数规格 Specification

型号 Model	RTA	单位 Unit	RTA10T	RTA15T	RTA20T	RTA25T	RTA30T	RTA40T	RTA50T	RTA60T	RTA80T	RTA100T	RTA125T	RTA150T	RTA175T	RTA200T
水流量 Water Flow		m ³ /h	7.81	11.7	15.62	19.51	23.4	31.21	39.24	46.8	62.64	78.12	97.56	117	136.8	156.24
风量 Wind Volume		CMM	85	140	160	200	230	280	330	420	450	700	830	950	1150	1250
音量 Sound Volume		Db	47	48	50	52	54	56.5	57.5	57	59	60	60	60	60	60
电机 Motor		KW	0.18	0.37	0.55	0.75	0.75	1.5	1.5	1.5	1.5	2.25	2.25	2.25	3.75	3.75
净重 Net Weight		KG	46	54	67	98	120	130	190	240	260	500	540	580	860	880
工作重量 Working Weight		KG	190	290	300	500	530	550	975	1250	1280	1600	1640	1680	1960	1980
塔高 Tower Height		MM	1725	1655	1930	1995	1840	1920	2125	2380	2475	2795	2945	2945	3515	3515
壳身 Casing		MM	1100	1000	1220	1220	1220	1250	1300	1330	1430	1460	1550	1650	1800	1900
入风口 Wind Entrance		MM	170	170	170	245	245	245	245	325	325	325	325	325	365	560
水盆 Water Base		MM	320	340	340	360	360	360	400	410	410	465	465	465	465	465
出入水口 Water In/ter/Outlet		WI/WO	40/40	50/50	50/50	80/80	80/80	80/80	80/80	100/100	100/100	125/125	125/125	150/150	150/150	150/150
风扇直径 Fan Diameter		MM	635	635	770	770	770	930	930	1180	1180	1450	1450	1450	1750	1750
底座直径 Base Diameter		MM	930	1200	1200	1420	1660	1660	1900	2100	2100	2914	2914	2914	3310	3310
溢水口 Over Flow/Drain		OF/DR	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	25/25	40/40	40/40
浮波/补水 Float/Supply		FV/QS	15/15	15/15	15/15	15/15	15/15	15/15	15/15	20/20	20/20	25/25	20/20	20/20	20/20	25/25
基础高度 Basic Height		MM	300	300	300	300	300	300	300	300	300	300	300	300	300	300
基础宽度 Basic Width		MM	300	300	300	300	300	300	300	300	300	300	300	300	300	300
水缸基础 Water Cabinet Base		MM										800	800	800	1000	1000
中心直径 Central Diameter		MM	473	779	779	1000	1110	1110	1350	1540	1540	2440	2440	2900	2900	3360
螺丝规格 Screw Specification		BC	M10	M10	M10	M10	M10	M10	M12	M12	M12	M12	M12	M12	M14	M14

方形冷却水塔 Square Cooling Tower

冷却塔采用优质PVC散热胶片、且设计形状更有效地延长高温水跟冷却风接触时间，所以冷却效果特佳。外壳底盘采用优质高强度玻璃纤维制成，外形美观，防腐及抵抗外界恶劣环境能力特强，转动及接合部分采用优质原材料加工，大大提高使用寿命及接合强度，客服部提供24小时技术及维修售后服务，将大大提高工作效率。

Our cooling tower adopts high quality PVC heat radiation films and the designed shape offilms effectively prolongs the contact time between high temperature water and the cooling air, therefore the cooling effect is excellent. The tower chassis, featuring anti--corrosion, strong abilityof resistance of vile weather and beautiful appearance made of high strength glassfiber, and itsrotation part and connection area is made of high quality raw materials, that greatly improves theservice life and connection strength.



参数规格 Specification

型号 Model	水流量 Water Flow Rate(m ³ /h)		水压 Water Press × 104 PA	尺寸 Dimensions					风机 Air Blower		重量 Weight	
	WBT			W	L	H	塔高 Tower Height	风筒高 Fan Stack Height	直径 Diameter	电机 Motor	净重 Net Weight	运行重 Working Weight
	28℃	27℃										
LD-100L	100	117	3.6	3200	1980	3700	3700	2300	700	4.0*1	0.86	2.26
LD-125L	125	146	3.8	3600	2310	3700	3700	2300	700	4.0*1	1.08	2.83
LD-150L	150	175	3.8	3800	2595	3700	3700	2300	700	4.0*1	1.18	3.55
LD-175L	175	205	4	3800	2915	3700	3700	2300	700	5.5*1	1.3	3.81
LD-200L	200	234	4	4300	3035	3700	3700	2300	700	5.5*1	1.6	4.02
LD-250L	250	292	3.8	3600	4620	3700	3700	2300	700	4.0*2	2.05	5.38
LD-300L	300	351	3.8	3800	5190	3700	3700	2300	700	4.0*2	2.24	6.75
LD-350L	350	409	4	3800	5830	3700	3700	2300	700	5.5*2	2.47	7.23
LD-400L	400	468	4	4300	6076	3700	3700	2300	700	5.5*2	3.04	7.65
LD-450L	450	526	4	3800	7785	3700	3700	2300	700	4.0*3	3.36	9.94
LD-500L	500	585	4	3600	9240	3700	3700	2300	700	4.0*4	4.1	10.75
LD-525L	525	614	4.2	3800	8745	3700	3700	2300	700	5.5*3	3.71	10.95
LD-600L	600	702	4.2	4300	9105	3700	3700	2300	700	5.5*3	4.56	11.45
LD-700L	700	819	4.2	3800	11660	3700	3700	2300	700	5.5*4	4.94	14.1
LD-800L	800	936	4.2	4300	12140	3700	3700	2300	700	5.5*4	6.08	15.27
LD-900L	900	1053	4.2	3800	15570	3700	3700	2300	700	4.0*6	6.73	18.2
LD-1000L	1000	1170	4.2	4300	15175	3700	3700	2300	700	5.5*5	7.6	19.93
LD-1200L	1200	1404	4.2	4300	18210	3700	3700	2300	700	5.5*6	9.12	22.5