

欧化干燥机

Euro-hopper Dryer

采用下吹式的欧化干燥机，料斗采用不锈钢制造，配备有“热气下吹”和“旋风排气”功能以及双层保温桶，特别适合搭配除湿机用来干燥工程塑料。

The Euro-hopper dryers adopt hot air down-blowing design and use stainless steel material hoppers to avoid contamination. With this design, they are also ideally suited for use with honeycomb dehumidifiers to dry engineering plastics.

特点 Features

- 采用微电脑控制，可精确控制温度；
- 特有下吹风管设计，能均匀分散热风，保持塑料干燥，温度稳定，提高干燥效率；
- 全数显式P.I.D.控制，LED状态显示；
- 有过热保护装置，可减少人为或机械故障所产生之意外；
- Microprocessor is used for accurate temperature control.
- Hot air down-blowing design ensures even distribution of hot air to maintain a steady temperature in the hopper and increase drying efficiency.
- Digital P.I.D temperature control with LED display, innovative design with sleek appearance.
- Overheat protection device can reduce accidents caused by man-made or mechanical failure.



参数规格 Specification

型号 Model	料筒容量 Hopper Capacity	干燥电热 Heating Power	风机 Blower	排风口径 Air outlet pipe dia	外形尺寸 Dimension	净重 Net weight	电压 Voltage
	单位 Unit	KG	KW	W	mm	MM	KG
DY-SH06	6	1.5	135	50	490*190*785	25	220V/1Phase
DY-SH12	12	2	150	50	540*435*850	35	220V/1Phase
DY-SH25	25	3	150	50	605*560*1240	50	220V/1Phase
DY-SH50	50	3.9	160	50	706*594*1410	75	380V/3Phase
DY-SH75	75	4.2	240	50	751*649*1520	105	380V/3Phase
DY-SH100	100	6.2	240	65	841*581*1670	125	380V/3Phase
DY-SH150	150	7	240	65	868*710*1800	160	380V/3Phase
DY-SH200	200	11	300	75	995*830*1930	210	380V/3Phase
DY-SH300	300	18	320	75	1160*975*2280	330	380V/3Phase
DY-SH400	400	20	360	90	1220*990*2330	365	380V/3Phase
DY-SH500	500	22	1500	90	1150*1045*2430	385	380V/3Phase
DY-SH600	600	24	1500	90	1210*1070*2540	400	380V/3Phase
DY-SH800	800	30	1500	127	1390*1120*2730	600	380V/3Phase
DY-SH1000	1000	36	2200	127	1525*1425*3670	650	380V/3Phase
DY-SH1200	1200	36	2200	150	1600*1510*3722	835	380V/3Phase
DY-SH1500	1500	40	2200	150	1730*1680*3880	900	380V/3Phase
DY-SH1800	1800	45	3700	219	1835*1680*4060	1005	380V/3Phase
DY-SH2000	2000	45	3700	219	1870*1710*4415	1130	380V/3Phase
DY-SH3000	3000	50	5000	219	2080*1920*4520	1650	380V/3Phase
DY-SH3500	3500	50	5500	219	2140*1976*4863	...	380V/3Phase
DY-SH4000	4000	60	7500	219	2192*2040*4936	...	380V/3Phase
DY-SH5000	5000	60	7500	219	2355*2160*5120	...	380V/3Phase